

MS612

6 x 12' - 3 Deck High Capacity Multi-Slope Screen Plant

MS612 6 X 12'- 3 Deck Screen Plant

High Capacity Multi-Slope Screen Plant





EASIER & SAFER SCREEN CHANGES

- · Less screen cloth
- Side access holes allow easier access for screen changes and maintenance. No need to enter the screen box.
- End tension
- No clamp bars
- 24 bolts, washers & nuts vs. 120 bolts, washers & nuts.

SIMPLIFIED MAINTENANCE & SERVICE

15 HP Electric Vibrating Motors

- No eccentric shaft, bearings, gears, seals, sheaves or guards to service, replace or store
- Adjustable counterweights (Throw)
- 3 ounces of grease per season vs. 200 tubes of grease or 50 gallons of oil.

MORE PRODUCTION

Than a 6'x 20'-3 Deck Screen Plant



BETTER • FASTER • SMALLER

THE SECRET IS EFFICIENT SCREENING

- Primary high angle panel results in rapid fines removal.
- Secondary lower angle panel results in accurate sizing and stratification associated with horizontal screening.

EASIER TO MOVE, SET UP AND USE





Adjustable Height Feed Hopper



Adjustable Height Head Section On Feed Conveyor



Adjustable Height Discharge Conveyor



12V Hydraulic Leveling



Hydraulic Screen & Sub-frame Raise & Lower

LESS HASSLE





ELRUS Walking Beam Suspension

- Increased strength & stability
- No springs to break



36"x12'-6" Cross Conveyors

- Allows product flexibility
- 7.5 HP Vandergraff motorized head pulleys
- 12" self-cleaning tail pulley
- Full length spillboards



Integral Rubber Hopper

- Smaller focal point for discharge
- No 20' under-screen hopper
- · Less flashing to maintain
- Shakes with screen. Self-cleaning



Motorized Head Pulley

- No drive guards, v-belts or motor mounts
- No adjustment required
- No external motor or gearbox
- Safer operation
- Less maintenance