

CONE PLANTS

CH660 CONE PLANT




24" WF Strapped and cambered main frame c/w Four (4) blocking legs ELRUS Heavy Duty HSS Tri-axle walking beam suspension Hydraulically positioned cone feed conveyor (6 way) Tramp metal protection magnet on feed conveyor Hydraulically raised & lowered cone discharge conveyor (self locking) 12 Volt Hydraulic plant leveling - Four (4) 50,000 lbs cylinders Floating subframe for cone & motor c/w 6 rubber compression mounts Rock box style under cone hopper Platform and stairway for cone inspection Complete guarding for cone drive and conveyors

Complete handrails and kick plates
Retractable access ladder to chassis
Clamp-on cone feed hopper c/w Overflow chute to return conveyor
Movable cable wraps mounted on hand rails
Air to Oil cooler and Positive air pump mounted on front of chassis

CONE CRUSHER:

Sandvik CH660 Hydrocone Crusher ASRi computer automated cone control 400 hp drive motor

CH440 CONE PLANT



21" WF Strapped and cambered main frame c/w Six (6) blocking legs ELRUS Heavy Duty HSS Tri-axle walking beam suspension Hydraulically positioned cone feed conveyor (4 way) Tramp metal protection magnet on feed conveyor Hydraulically raised & lowered cone discharge conveyor (self locking) 12 Volt Hydraulic plant leveling - Two (2) 50,000 lbs cylinders Floating subframe for cone & motor c/w 6 rubber compression mounts Rock box style under cone hopper Platform and stairway for cone inspection Complete guarding for cone drive and conveyors

Fixed walkway on both sides of cone and across front of chassis
Complete handrails and kick plates
Retractable access ladder to chassis
Clamp-on cone feed hopper c/w Overflow chute to return conveyor
Movable cable wraps mounted on hand rails
Air to Oil cooler and Positive air pump mounted on front of chassis

CONE CRUSHER:

Sandvik CH440 Hydrocone Crusher ASRi computer automated cone control 300 hp drive motor

CH430 CONE PLANT **CHASSIS FEATURES:** Complete handrails and kick plates Retractable access ladder to chassis 18" WF Strapped and cambered main frame c/w Six (6) blocking legs Clamp-on cone feed hopper c/w Overflow chute to return conveyor ELRUS Heavy Duty HSS Tandem axle walking beam suspension Movable cable wraps mounted on hand rails Hydraulically positioned cone feed conveyor (4 way) Air to Oil cooler and Positive air pump mounted on front of chassis

18" WF Strapped and cambered main frame c/w Six (6) blocking legs ELRUS Heavy Duty HSS Tandem axle walking beam suspension Hydraulically positioned cone feed conveyor (4 way) Tramp metal protection magnet on feed conveyor Hydraulically raised & lowered cone discharge conveyor (self locking) 12 Volt Hydraulic plant leveling - Two (2) 50,000 lbs cylinders Floating subframe for cone & motor c/w 4 rubber compression mounts Rock box style under cone hopper

Complete guarding for cone drive and conveyors Fixed walkway on both sides of cone and across front of chassis

CONE CRUSHER:

Sandvik CH430 Hydrocone Crusher ASRi computer automated cone control 200 hp drive motor





24" WF Strapped and cambered main frame c/w Six (6) blocking legs ELRUS Heavy Duty HSS Tri-axle walking beam suspension Hydraulically raised & lowered cone discharge conveyor (self locking) 12 Volt Hydraulic plant leveling - Four (4) 50,000 lbs cylinders Floating subframe for cone & motor c/w 6 rubber compression mounts Rock box style under cone hopper Platform and stairway for cone inspection Complete guarding for cone drive and conveyors Fixed walkway on both sides of cone and across front of chassis Complete handrails and kick plates

Clamp-on cone feed hopper

Movable cable wraps mounted on hand rails

Air to Oil cooler and Positive air pump mounted on front of chassis

GYRATORY CRUSHER:

Sandvik CS660 Hydrocone Crusher ASRi computer automated cone control 400 hp drive motor



CHASSIS FEATURES:

21" WF Strapped and cambered main frame c/w Six (6) blocking legs ELRUS Heavy Duty HSS Tri-axle walking beam suspension Hydraulically positioned cone feed conveyor (Optional) Tramp metal protection magnet on feed conveyor Hydraulically raised & lowered cone discharge conveyor (self locking) 12 Volt Hydraulic plant leveling - Four (4) 50,000 lbs cylinders Floating subframe for cone & motor c/w 4 rubber compression mounts Rock box style under cone hopper Platform and stairway for cone inspection Complete guarding for cone drive and conveyors

Fixed walkway on both sides of cone and across front of chassis Complete handrails and kick plates Retractable access ladder to chassis Clamp-on cone feed hopper Movable cable wraps mounted on hand rails Air to Oil cooler and Positive air pump mounted on front of chassis

GYRATORY CRUSHER:

Sandvik CS440 Hydrocone Crusher ASRi computer automated cone control 300 hp drive motor

CS430 CONE



ELRUS Heavy Duty HSS Sixteen wheel suspension c/w booster
42" front discharge conveyor c/w hydraulic raise & lower and fold
12 Volt Hydraulic plant leveling - Four (4) 50,000 lbs cylinders
Floating subframe for cone & motor c/w 4 rubber compression mounts
Rock box style under cone hopper
Platform and stairway for cone inspection


Complete guarding for cone drive and conveyors

Fixed walkway on both sides of cone and screen and across front of chassis

Complete handrails and kick plates

GYRATORY CRUSHER:

Sandvik CS430 Hydrocone Crusher ASRi computer automated cone control 200 hp drive motor Primary Scalping 6' x 20' 2 Deck Horizontal Screen 60" reversible under screen conveyor on slide 42" cross conveyor c/w fold







SANDVIK HYDROCONES



The ASRi will optimize performance of your Hydrocone crushers with the most up-to-date technology in order to best monitor your crushing equipment minute by minute. By using the latest intelligent crushing control system—the ASRi—you can choose which systems to monitor and make crusher settings on the fly.

Extremely user-friendly; the ASRi is controlled with a touch screen and a color Graphical User Interface (GUI) that includes cables and transducers so you may check connections. The ASRi has a built-in instruction manual and a number of automated functions.



The ASRi gives you the control to protect your crushing equipment from damage while increasing productivity; receiving the highest degree of product reduction; and getting better cubical products.



FEATURES



Adjustable Feed Height of Feed Conveyor



Movable Wire Wraps • Oil Cooler • Positive Air Pressure Pump



Feed Tub c/w Overflow Chute



Floating Cone and Motor Base on Rubber Mounts



Front Side Shift of Feed Conveyor with Adjustable Height



Heavy Duty Axle System



Hydraulic Levelling and Full Guarding




Hydraulic Raise/Lower Discharge Conveyor



Hydraulic Levelling System
External Oil Tank Heater Tube



Rear Hydraulic Side Shift of Feed Conveyor




Rock Box Style under Cone Hopper



Tramp Metal Protection Magnet







Aylmer, ON. Production Facility 702 Talbot Street W Aylmer, ON N5H



Eloy, AZ Production Facility 924 North Tweedy RD, Eloy AZ 85231

Head Office & Manufacturing Facilities

4409 Glenmore Trail, S.E. Calgary, AB T2C 2R8 PH: (403) 279-7741 FX: (403) 236-51511 888 535 7877 info@elrus.com



19066-95A Avenue Surrey BC, V4N 4P2 604-888-8499 Ph: TF: 604-484-3303 Fax: 604-513-2452 Email: bc@elrus.com



8401 39 Street, Leduc, AB T9E 8M7 Ph: 780-980-5600 TF: 877-484-3303 Fax: 780-489-3041 Email:



843 60th St E. Saskatoon, SK S7K 5Z7 Ph: 306-668-0890 TF: 855-668-0890 Fax: 306-668-0899 edmonton@elrus.com Email: saskatoon@elrus.com



Hwy 101 & Sturgeon Rd. N. Box 6 Group 220, RR2 Winnipeg, MB R3C 2E6 Ph: 204-888-5588 TF: 855-588-5588 Fax: 204-888-4740

Email: winnipeg@elrus.com



170 Turnbull Ct. Cambridge, ON N1T 1J2 Ph: 519-624-6500 TF: 866-795-1188 Fax: 519-624-6505

Email: edmonton@elrus.com



1217 140th Ave. Court East Sumner, WA 98390 Ph: 206-713-1928 Email: sumner@elrus.com