

30" x 36" Belt Feeder



Chassis:

- 16" WF main frame c/w single axle
- Four (4) 11 x 22.5 wheels & tires

Hopper:

- 7'6" x 12' self relieving hopper assembly - 1/4" plate
- Approx. 12 cu. yd. capacity

Feed Belt:

- 30" belt feeder cartridge
- 5" steel rollers
- 12" rubber lagged head pulley
- 12" self cleaning tail pulley c/w 2 7/16" take up bearings and shaft assembly
- Goodyear 30" 3-ply 1/4" x 1/16" conveyor belting with vulcanised splice Dodge 4207 reducer
- 5 HP T.E.F.C. electric motor drive

36" x 33' Delivery Conveyor - Channel Frame:

- 36" adjustable end delivery conveyor
- Goodyear 36" wide 3-ply 3/16" x 1/16" conveyor belting with vulcanised splice
- 10 HP T.E.F.C. electric motor
- Dodge 3203 speed reducer and v belt drive
- 12" rubber lagged head pulley c/w 2 7/16" pillow block bearings & shaft
- 12" crowned self cleaning tail pulley c/w 2 7/16" take up assemblies & shaft

Optional Equipment:

- Hydraulic Side Dumping Grizzly
- Flat bar round bar grizzly
- 6" fixed spacings (adjustable optional)
- 5 hp hydraulic dumping system remote controlled from tower

30"x 36" Belt Feeder G/A

