

6'x20'-3 Deck Feeder Screen Plant



Chassis

- 18" and 21" WF Dropped mainframe
- Eight (8) blocking legs
- Tri axle walking beam suspension 60" centres

6 X 20 - 3 Deck Screen @ 15° - 332 Series

- 1/2" Side plates
- 160 mm. Spherical roller bearings
- Heavy duty decks
- Counter-weights = 31/2" thick, shim adjustable
- Counterweight guards
- Eight (8) 11/4" coil springs c/w extra wide mounting pads
- Two (2) side tension springs

Hopper

- 8' x 13' Self relieving hopper assembly 1/4" plate
- Approximately 15 cubic yard capacity

Hydraulic Side Dumping Grizzly

- Heavy duty adjustable bars
- Heavy duty 4" diameter dumping cylinders
- 10 HP C-flange Electric motor, 11 GPM pump and Yuken controller
- 36" Feed Belt
- 42" x 45' Overhead Conveyor
- 60" x 34' Underscreen Conveyor
- Two (2) 36" x 12'6" Cross Conveyors
- Hydraulic Levelling System

Optional Equipment

- Torspec vari-speed motor c/w controller & Eurodrive reducer
- Variable Speed Frequency Controller
- End Tension Carry Decks
- Hydraulic Fold on Cross Conveyors over 12'6"

6'x20'-3 Deck Feeder Screen Plant G/A

